

TITAN

Collection

PRODUCT CHARACTERISTICS

- Corrugated profile

The Rialux siding panels of the **Titan Collection** are entirely composed of aluminum. The Rialux siding panels stand out due to their light weight properties, rust resistance and installation ease.

PRODUCT DETAILS	DIMENSIONS
Length	150 inches
Height covered	12 inches
Thickness - depth	0.40 inches
Weight (per panel)	6.5 lbs
Caliber	21 thousandth
Panel	1 panel = 12.5 ft ²

INSTALLATION SURFACES

- On wood furring
(16 inches center to center)
- On metal furring
(16 inches center to center)

DIRECTIONS OF INSTALLATION

- Horizontal laying
- Vertical laying

PACKAGING


Quantity per box	Sold individually
Area covered per panel	12.5 ft ²

NOTE

Please refer to the building codes for installation details.

TITAN

Collection



SCREWS

Screw in the middle of each opening provided for this purpose and in a moderate way. Make sure that the result is satisfying every 3 or 4 rows installed.

ASSEMBLY

Overlap the panels one over the other, then screw them in place.

MATERIAL VERIFICATION

The contents of every box must be inspected upon reception. All material installed constitutes acceptance of product.

MOULDINGS AND ACCESSORIES

The aluminum siding manufacturer Rialux also offers Drip cap, J-Trim, as well as interior and exterior corners.


A drip cap is required to divert water around windows and doors.

HANDLING BOXES

Always lift from both ends and keep the box straight at all times. Do not lift from the middle to avoid damaging or warping the product.



COLORS




MATTE BLACK MATTE SILVER

*THIS PROFILE IS ALSO AVAILABLE IN BOSCO COLORS.

FIRE RESISTANCE

The aluminum siding panels of the Rialux **Titan Collection** are classified as a zero flammability hazard, according to the NFPA Rating Explanation Guide.



SCALE 1:2