
Technical details





TITAN

Collection

PRODUCT CHARACTERISTICS

· Corrugated profile

The Rialux siding panels of the **Titan Collection** are entirely composed of aluminum. The Rialux siding panels stand out due to their light weight properties, rust resistance and installation ease.

PRODUCT DETAILS	DIMENSIONS
Length	150 inches
Height covered	12 inches
Thickness - depth	0.40 inches
Weight (per panel)	3.30 lbs
Screw holes	3/4 in x 1/8 in (19mm x 3.2mm)
Screw hole intervals	3 1/4 in (82.5mm)
Caliber	23 thousandth
Panel	1 panel = 12.5 ft²

PACKAGING	
Quantity per box	20 panels of 150 in
Area covered per box	250 ft ²
Box dimension	152 x 7 3/4 x 4 7/8 inches
Box weight	66 lbs

NOTE

Please refer to the building codes for installation details.

INSTALLATION SURFACES

- On wood furring
 (16 inches center to center)
- On metal furring (16 inches center to center)

DIRECTIONS OF INSTALLATION

- Horizontal laying
- Vertical laying

FIXING PROCEDURE

 Screw every 16 inches in the middle of each opening provided for this purpose.
 Use stainless steel screws.

CONTINUED ON PAGE 12

TITAN

Collection



SCREWS

Screw in the middle of each opening provided for this purpose and in a moderate way. It is important not to use pressure towards the bottom or the top while screwing. Make sure that the result is satisfying every 3 or 4 rows installed. To ensure installation quality, remove the protective film from the coating throughout and make corrections if necessary.

ASSEMBLY

Overlap the panels one over the other, then screw them in place.

MATERIAL VERIFICATION

The contents of every box must be inspected upon reception. All material installed constitutes acceptance of product.

MOULDINGS AND ACCESSORIES

The aluminum siding manufacturer Rialux also offers Starter strip, Drip cap, J-Trim, as well as interior and exterior corners.

Carefully install the starter strip as a hidden fastener at the base of the walls behind the Rialux profiles. A drip cap is required to divert water around windows and doors.


HANDLING BOXES

Always lift from both ends and keep the box straight at all times. Do not lift from the middle to avoid damaging or warping the product.





COLORS



*THIS PROFILE IS ALSO AVAILABLE IN BOSCO COLORS.

FIRE RESISTANCE

The aluminum siding panels of the Rialux **Titan Collection** are classified as a zero flammability hazard, according to the NFPA Rating Rating Explanation Guide.



SCALE 1:2

RIALUX.COM 12