



# BOLTON

## Collection

### PRODUCT CHARACTERISTICS

- Board & Batten profile

The Rialux siding panels of the **Bolton Collection** are entirely composed of aluminum. The Rialux siding panels stand out due to their light weight properties, rust resistance and installation ease. The panels have a surface that resembles natural wood, which will surely enhance the look of your project.

PRODUCT DETAILS	DIMENSIONS
Length	150 inches
Height covered	12 inches
Thickness - depth	1.063 inches
Weight (per panel)	6.5 lbs
Screw holes	0.75 in x 0.1875 in (19mm x 4.8mm)
Screw hole intervals	1.5 in (38.1mm)
Caliber	27 thousandth
Panel	1 panel = 12.5 ft <sup>2</sup>

PACKAGING	
Quantity per box	10 panels of 150 in
Area covered per box	125 ft <sup>2</sup>
Box dimension	152 x 16 x 4 1/8 inches
Box weight	65 lbs

### NOTE

Please refer to the building codes for installation details.

### MIXING THE SHADES

Rialux **Bolton Collection** panels are composed of many different shades in every color offered. Therefore, it is extremely important to mix the shades during installation to ensure an even distribution of the different shades throughout the surface. Make sure to validate that the results are satisfying every 3 or 4 rows installed.

### INSTALLATION SURFACES

- On wood furring  
(16 inches center to center)
- On metal furring  
(16 inches center to center)

### DIRECTIONS OF INSTALLATION

- Vertical laying

### FIXING PROCEDURE

- Screw every 16 inches in the middle of each opening provided for this purpose. Use stainless steel screws.

# BOLTON

## Collection



### SCREWS

Screw in the middle of each opening provided for this purpose and in a moderate way. It is important not to use pressure towards the bottom or the top while screwing. Make sure that the result is satisfying every 3 or 4 rows installed. To ensure installation quality, remove the protective film from the coating throughout and make corrections if necessary.

### ASSEMBLY

Use a transition molding to overlap the panels.

### MATERIAL VERIFICATION

The contents of every box must be inspected upon reception. All material installed constitutes acceptance of product.

### MOULDINGS AND ACCESSORIES

The aluminum siding manufacturer Rialux also offers Starter strip, Drip cap, J-Trim, as well as interior and exterior corners.

Carefully install the starter strip as a hidden fastener at the base of the walls behind the Rialux profiles. A drip cap is required to divert water around windows and doors.

### HANDLING BOXES

Always lift from both ends and keep the box straight at all times. Do not lift from the middle to avoid damaging or warping the product.



### COLORS



BARK

BIRCH

EBONY

SIENNA

GREY OAK



DRIFTWOOD

DARK WALNUT

NORDIC CEDAR

MATTE BLACK

BALSA\*

### FIRE RESISTANCE

The aluminum siding panels of the Rialux **Bolton Collection** are classified as a zero flammability hazard, according to the NFPA Rating Explanation Guide.

\*THE BALSA COLOR IS AVAILABLE WHILE SUPPLIES LAST.